

PL-2006

Pressure Sensitive Adhesive

Stick with Valco®



Ordering Information:

Part Number: 713xx081, 31 lb. box

Product Type:

Pressure Sensitive Adhesive

Physical Properties:

Appearance: Amber

Viscosity: 16,750 cps at 250° F

7,500 cps at 275° F

4,900 cps at 325° F

1,750 cps at 350° F

Form: Pillow

Bond: Medium

Peel Strength: Medium

Operating Temperatures:

Target: 325° F

Typical: 315° F to 350° F

Suggested Use:

Product Assembly / Tipping

- Temporary bond of paper and plastic with no fiber tear

Product Features:

- Quick setting ideal for most applications.
- "Peelable" or removable once set.
- Meets composition requirements of Indirect Food Additives Regulation 21 CFR 175.105.

Operating Conditions:

- Suitable for all gear drive pumps.
- Suitable for piston pumps with spring loaded ball checks.
- Applied with any standard pneumatic or electric applicator.
- Air open/air close application reduces stringing and trailing.
- Suitable for wheel based applications.

Precautions:

- Material applied hot - appropriate clothing or eye protection should be used.
- Use with adequate ventilation to remove melt fumes or vapors being generated.
- Keep containers and pre-melters covered.
- Do not mix with other adhesives.



Valco Cincinnati, Inc.
411 Circle Freeway Drive
Cincinnati, OH 45246
Tel: (513) 874-6550
Fax: (513) 874-3612
www.valcocincinnatiinc.com
sales@valcocincinnatiinc.com

Shure-Glue/Melton
457 Circle Freeway Drive
Cincinnati, Ohio 45246
Tel: 513.874.5581
Fax: 513.874.8318
sales@shure-glue.com
www.shure-glue.com

Vansco Systems, Inc.
2652 Lashbrook Avenue
South El Monte, CA 91733
Tel: 626.448.7611
Tel: 626.448.0221
sales@vansco.com
www.vansco.com

Valco Cincinnati, Ltd.
Unit 7-8
Hortonwood 32
Telford, TF1 7YN
Tel: (44) 1952 677911
Fax: (44) 1952 677945
sales@valco.co.uk
info@meltondirect.com

Valco Cincinnati GmbH
Storkower Strasse 6
D-15749 Gallun
Tel: (49) 33764 8700
Fax: (49) 33764 87070
info@valcogmbh.de
www.valcogmbh.de